



Technical support provided by,



P: 03 9847 0177 E: solutions@stingeraustralia.com.au



Unclip and remove panel under OEM head unit



2013-Up: VW Golf 7



CTKVW08 Contents

- 1x Fascia Panel
- 1x Menu Button Panel
- 1x Mounts Brackets
- 1x Screws

- 1x Vehicle Integration Interface 1x Vehicle T Harness
- 1x Camera T Harness
- 1x SWC Patch Lead



Unclip OEM head unit panel



Unclip air vents (specail VW tool may be required)

Remove OEM head unit panel by pulling it torward your direction



Insert radio release keys Remove OEM head unit



All installation work must be performed by a qualified professional installer only. The manufacturer / dealer is not liable for any kind of incidential or indirect damages.








Several plastic parts must be cut and removed in order clear space for 2-DIN head unit

Cut plastic (see arrows) and remove it



Cut plastic bridge underneath removed plastic (see arrows)





Mount mounting brackets to double DIN head unit

pre-assembly Unit and Brackets









Remove air vent unit from OEM panel

Mount air vent unit to double DIN head unit

Connect all required circuit points. Mount double DIN head unit to dashboard. Place facia plate. Reinstall everything in reverse order to finish installation



VEHICLE INTEGRATION INTERFACE

The Connects2 Infodapter for VW MIB platform vehicles allows vehicle information such as climate control, parking sensors and heated seats to be displayed on any aftermarket head unit with rear camera input. The Infodapter also allows the use of the steering wheel controls with almost every steering wheel control compatible head unit on the market.


DIP SWITCH SETTINGS


See Fia 1.

Up = Off, Down = On

- 1: On = Pioneer head units. Off = All other head units
- 2: Setting for reverse camera. On = PAL, Off = NTSC. The default setting is Off (NTSC).
- **3:** Resets the display settings back to default. If the display settings have been manipulated in a way that it is no longer possible to make adjustments, change the DIP switch #3 from Off to On and back. This will reset the screen settings to the factory defaults. During this procedure the screen background will change to red. While the background is red, no settings can be made.
- 4: Not applicable. (This should be kept in the Up/Off position)

Interface Connections







Facia/Steering Wheel Controls



Configuration Menu

To access the menu, push the 'MENU' button on the fascia panel (Fig.3) and use the UP and DOWN buttons to navigate. Use the OK button to select and Back to go back or exit.

The Car button will allow access to the vehicle trip computer.

Configuration Menu **Vehicle Settings** Infodapter Settings Language Version < Back


Vehicle Settings

Vehicle settings can be adjusted via the menu. All vehicle setup options that were available with the original head unit, are now available through the aftermarket head unit. See the vehicle handbook for more information regarding these features.

Vehicle Settings ESC System Tyre Driver Assistance Parking and Manoeuvering Light Mirrors and Wipers

Infodapter Settings

Screen Size/Position -Make sure all 4 corner markers are touching the corners of the aftermarket head unit display. Note that you may need to adjust the screen size/ position to avoid any warning messages displayed on the aftermarket head unit.



Configuration Menu...continued

 Picture Settings -Adjust Brightness, contrast and colour saturation.

Infodapter Settings

Screen Size/Position **Picture Settings** Preferences <Back

Preferences

Riaht

Preferences -

Driver Position - Select Left or Right depending upon vehicle configuration.

Camera Connected - Select Yes if an optional camera is connected.

Reverse Priority* - Select which image (Camera or Park Assist) will be shown by default when reversing. The driver can select the desired image by pushing the Source button (Fig.3) while reversing. (*Note this option is only available when Camera Connected is set to Yes)

Park Brake Source - Set to Speed, Brake or Always On.

Climate - Select how long the climate display should be shown on the head unit when adjusted. Select between the range of 3 seconds and 30 seconds.

Restore factory settings - Reverts all Infodapter settings to factory defaults. (This does not restore vehicle settings)



Drivina Mode -The driving mode button can be used as normal. The graphic for the mode will be shown on the head unit.



Park Assist -The park assist button can be used as normal to activate/decactivate park assist. The graphic will be shown on the head unit.

Legal Information

Please consult the relevant road traffic laws governing the country in which this product is being operated. No liability is accepted for material damage, loss or personal injury, directly or indirectly, from installation and operation of this product. This product should only be operated when safe to do so.

Driver Position Camera Connected

Yes Reverse Priority Park Assist Park Brake Source Speed Climate 55

Restore factory settings < Back

Technical support provided by, P: 03 9847 0177 E: solutions@stingeraustralia.com.au